

# RingsForHomalg

**Rings in External Computer Algebra Systems for the GAP-Package  
homalg**

Version 2009.11.09

November 2009

**Mohamed Barakat**

**Simon Goertzen  
Markus Kirschmer  
Markus Lange-Hegermann  
Max Neunhöffer  
Daniel Robertz**

*(this manual is still under construction)*

This manual is best viewed as an HTML document. The latest version is available ONLINE at:

<http://homalg.math.rwth-aachen.de/~barakat/RingsForHomalg/chap0.html>

An OFFLINE version should be included in the documentation subfolder of the package. This package is part of the homalg-project:

<http://homalg.math.rwth-aachen.de/index.php/core-packages/ringsforhomalg>

**Mohamed Barakat**

— Email: [barakat@mathematik.uni-kl.de](mailto:barakat@mathematik.uni-kl.de)

— Homepage: <http://wwwb.math.rwth-aachen.de/~barakat/>

— Address: Department of Mathematics,  
University of Kaiserslautern,  
67653 Kaiserslautern,  
Germany

**Simon Goertzen** — Email: [simon.goertzen@rwth-aachen.de](mailto:simon.goertzen@rwth-aachen.de)

— Homepage: <http://wwwb.math.rwth-aachen.de/~simon>

— Address: Lehrstuhl B für Mathematik, RWTH Aachen, Templer-  
graben 64, 52056 Aachen, Germany

**Markus Kirschmer** — Email: [markus.kirschmer@math.rwth-aachen.de](mailto:markus.kirschmer@math.rwth-aachen.de)

— Homepage: <http://www.math.rwth-aachen.de/~Markus.Kirschmer>

— Address: Lehrstuhl D für Mathematik, RWTH Aachen, Templer-  
graben 64, 52056 Aachen, Germany

**Markus Lange-Hegermann** — Email: [markus.lange-hegermann@rwth-aachen.de](mailto:markus.lange-hegermann@rwth-aachen.de)

— Homepage: <http://wwwb.math.rwth-aachen.de/~markus>

— Address: Lehrstuhl B für Mathematik, RWTH Aachen, Templer-  
graben 64, 52056 Aachen, Germany

**Max Neunhöffer** — Email: [daniel@momo.math.rwth-aachen.de](mailto:daniel@momo.math.rwth-aachen.de)

— Homepage: <http://wwwb.math.rwth-aachen.de/~daniel>

— Address: St Andrews University, School of Mathematics and  
Statistics, Mathematical Institute, North Haugh, St An-  
drews, Fife KY16 9SS, Scotland, UK

**Daniel Robertz** — Email: [daniel@momo.math.rwth-aachen.de](mailto:daniel@momo.math.rwth-aachen.de)

— Homepage: <http://wwwb.math.rwth-aachen.de/~daniel>

— Address: Lehrstuhl B für Mathematik, RWTH Aachen, Templer-  
graben 64, 52056 Aachen, Germany

## **Copyright**

© 2007-2009 by Mohamed Barakat, Simon Görtzen, Markus Kirschmer, Markus Lange-Hegermann, Max Neunhöffer, and Daniel Robertz.

This package may be distributed under the terms and conditions of the GNU Public License Version 2.

# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
1.1	Ring Constructions for Supported External Computer Algebra Systems . . . . .	5
1.1.1	external GAP . . . . .	5
1.1.2	Singular . . . . .	6
1.1.3	MAGMA . . . . .	6
1.1.4	Macaulay2 . . . . .	7
1.1.5	Sage . . . . .	7
1.1.6	Maple . . . . .	8
<b>2</b>	<b>Installation of the RingsForHomalg Package</b>	<b>9</b>
<b>3</b>	<b>The Ring Table</b>	<b>10</b>
3.1	An Example for a Ring Table - Singular . . . . .	10
3.1.1	BasisOfRowModule (in the homalg table for Singular) . . . . .	10
3.1.2	BasisOfRowModule (Singular macro) . . . . .	10
3.1.3	BasisOfColumnModule (in the homalg table for Singular) . . . . .	11
3.1.4	BasisOfColumnModule (Singular macro) . . . . .	11
3.1.5	DecideZeroRows (in the homalg table for Singular) . . . . .	11
3.1.6	DecideZeroRows (Singular macro) . . . . .	12
3.1.7	DecideZeroColumns (in the homalg table for Singular) . . . . .	12
3.1.8	DecideZeroColumns (Singular macro) . . . . .	13
3.1.9	SyzygiesGeneratorsOfRows (in the homalg table for Singular) . . . . .	13
3.1.10	SyzygiesGeneratorsOfRows (Singular macro) . . . . .	14
3.1.11	SyzygiesGeneratorsOfColumns (in the homalg table for Singular) . . . . .	14
3.1.12	SyzygiesGeneratorsOfColumns (Singular macro) . . . . .	14
3.1.13	BasisOfRowsCoeff (in the homalg table for Singular) . . . . .	15
3.1.14	BasisOfRowsCoeff (Singular macro) . . . . .	15
3.1.15	BasisOfColumnsCoeff (in the homalg table for Singular) . . . . .	15
3.1.16	BasisOfColumnsCoeff (Singular macro) . . . . .	16
3.1.17	DecideZeroRowsEffectively (in the homalg table for Singular) . . . . .	16
3.1.18	DecideZeroRowsEffectively (Singular macro) . . . . .	17
3.1.19	DecideZeroColumnsEffectively (in the homalg table for Singular) . . . . .	17
3.1.20	DecideZeroColumnsEffectively (Singular macro) . . . . .	18
3.1.21	RelativeSyzygiesGeneratorsOfRows (in the homalg table for Singular) . . . . .	18
3.1.22	RelativeSyzygiesGeneratorsOfRows (Singular macro) . . . . .	19
3.1.23	RelativeSyzygiesGeneratorsOfColumns (in the homalg table for Singular) . . . . .	19

3.1.24	<a href="#">RelativeSyzygiesGeneratorsOfColumns (Singular macro)</a>	20
3.1.25	<a href="#">ReducedSyzygiesGeneratorsOfRows (in the homalg table for Singular)</a>	20
3.1.26	<a href="#">ReducedSyzygiesGeneratorsOfRows (Singular macro)</a>	20
3.1.27	<a href="#">ReducedSyzygiesGeneratorsOfColumns (in the homalg table for Singular)</a>	21
3.1.28	<a href="#">ReducedSyzygiesGeneratorsOfColumns (Singular macro)</a>	21

# Chapter 1

## Introduction

This package is part of the homalg project [ht09]. The role of the package is described in the manual of the homalg package.

### 1.1 Ring Constructions for Supported External Computer Algebra Systems

Here are some of the supported ring constructions:

#### 1.1.1 external GAP

```
Example
gap> ZZ := HomalgRingOfIntegersInExternalGAP( );
<A homalg external ring residing in the CAS GAP>
gap> Display( ZZ );
Z
gap> F2 := HomalgRingOfIntegersInExternalGAP( 2, ZZ );
<A homalg external ring residing in the CAS GAP>
gap> Display( F2 );
GF(2)
```

`F2 := HomalgRingOfIntegersInExternalGAP( 2 )` would launch another GAP.

```
Example
gap> Z4 := HomalgRingOfIntegersInExternalGAP( 4, ZZ );
<A homalg external ring residing in the CAS GAP>
gap> Display( Z4 );
Z/4Z
gap> Z_4 := HomalgRingOfIntegersInExternalGAP( ZZ ) / 4;
<A homalg residue class ring>
gap> Display( Z_4 );
Z/( 4 )
gap> Q := HomalgFieldOfRationalsInExternalGAP( ZZ );
<A homalg external ring residing in the CAS GAP>
gap> Display( Q );
Q
```

### 1.1.2 Singular

Example

```
gap> F2 := HomalgRingOfIntegersInSingular( 2 );
<A homalg external ring residing in the CAS Singular>
gap> Display( F2 );
GF(2)
gap> Q := HomalgFieldOfRationalsInSingular( F2 );
<A homalg external ring residing in the CAS Singular>
gap> Display( Q );
Q
```

`Q := HomalgFieldOfRationalsInSingular( )` would launch another Singular.

Example

```
gap> F2xyz := F2 * "x,y,z";
<A homalg external ring residing in the CAS Singular>
gap> Display( F2xyz );
GF(2)[x,y,z]
gap> Qxyz := Q * "x,y,z";
<A homalg external ring residing in the CAS Singular>
gap> Display( Qxyz );
Q[x,y,z]
```

### 1.1.3 MAGMA

Example

```
gap> ZZ := HomalgRingOfIntegersInMAGMA( );
<A homalg external ring residing in the CAS MAGMA>
gap> Display( ZZ );
Z
gap> F2 := HomalgRingOfIntegersInMAGMA( 2, ZZ );
<A homalg external ring residing in the CAS MAGMA>
gap> Display( F2 );
GF(2)
```

`F2 := HomalgRingOfIntegersInMAGMA( 2 )` would launch another MAGMA.

Example

```
gap> Z_4 := HomalgRingOfIntegersInMAGMA( ZZ ) / 4;
<A homalg residue class ring>
gap> Display( Z_4 );
Z/( 4 )
gap> Q := HomalgFieldOfRationalsInMAGMA( ZZ );
<A homalg external ring residing in the CAS MAGMA>
gap> Display( Q );
Q
gap> F2xyz := F2 * "x,y,z";
<A homalg external ring residing in the CAS MAGMA>
gap> Display( F2xyz );
GF(2)[x,y,z]
gap> Qxyz := Q * "x,y,z";
<A homalg external ring residing in the CAS MAGMA>
gap> Display( Qxyz );
Q[x,y,z]
```

### 1.1.4 Macaulay2

Example

```
gap> ZZ := HomalgRingOfIntegersInMacaulay2( );
<A homalg external ring residing in the CAS Macaulay2>
gap> Display( ZZ );
Z
gap> F2 := HomalgRingOfIntegersInMacaulay2( 2, ZZ );
<A homalg external ring residing in the CAS Macaulay2>
gap> Display( F2 );
GF(2)
```

`F2 := HomalgRingOfIntegersInMacaulay2( 2 )` would launch another Macaulay2.

Example

```
gap> Z_4 := HomalgRingOfIntegersInMacaulay2( ZZ ) / 4;
<A homalg residue class ring>
gap> Display( Z_4 );
Z/( 4 )
gap> Q := HomalgFieldOfRationalsInMacaulay2( ZZ );
<A homalg external ring residing in the CAS Macaulay2>
gap> Display( Q );
Q
gap> F2xyz := F2 * "x,y,z";
<A homalg external ring residing in the CAS Macaulay2>
gap> Display( F2xyz );
GF(2)[x,y,z]
gap> Qxyz := Q * "x,y,z";
<A homalg external ring residing in the CAS Macaulay2>
gap> Display( Qxyz );
Q[x,y,z]
```

### 1.1.5 Sage

Example

```
gap> ZZ := HomalgRingOfIntegersInSage( );
<A homalg external ring residing in the CAS Sage>
gap> Display( ZZ );
Z
gap> F2 := HomalgRingOfIntegersInSage( 2, ZZ );
<A homalg external ring residing in the CAS Sage>
gap> Display( F2 );
GF(2)
```

`F2 := HomalgRingOfIntegersInSage( 2 )` would launch another Sage.

Example

```
gap> Z_4 := HomalgRingOfIntegersInSage( ZZ ) / 4;
<A homalg residue class ring>
gap> Display( Z_4 );
Z/( 4 )
gap> Q := HomalgFieldOfRationalsInSage( ZZ );
<A homalg external ring residing in the CAS Sage>
gap> Display( Q );
Q
```



```

gap> F2x := F2 * "x";
<A homalg external ring residing in the CAS Sage>
gap> Display( F2x );
GF(2)[x]
gap> Qx := Q * "x";
<A homalg external ring residing in the CAS Sage>
gap> Display( Qx );
Q[x]

```

### 1.1.6 Maple

Example

```

gap> ZZ := HomalgRingOfIntegersInMaple( );
<A homalg external ring residing in the CAS Maple>
gap> Display( ZZ );
Z
gap> F2 := HomalgRingOfIntegersInMaple( 2, ZZ );
<A homalg external ring residing in the CAS Maple>
gap> Display( F2 );
GF(2)

```

`F2 := HomalgRingOfIntegersInMaple( 2 )` would launch another Maple.

Example

```

gap> Z4 := HomalgRingOfIntegersInMaple( 4, ZZ );
<A homalg external ring residing in the CAS Maple>
gap> Display( Z4 );
Z/4Z
gap> Z_4 := HomalgRingOfIntegersInMaple( ZZ ) / 4;
<A homalg residue class ring>
gap> Display( Z_4 );
Z/( 4 )
gap> Q := HomalgFieldOfRationalsInMaple( ZZ );
<A homalg external ring residing in the CAS Maple>
gap> Display( Q );
Q
gap> F2xyz := F2 * "x,y,z";
<A homalg external ring residing in the CAS Maple>
gap> Display( F2xyz );
GF(2)[x,y,z]
gap> Qxyz := Q * "x,y,z";
<A homalg external ring residing in the CAS Maple>
gap> Display( Qxyz );
Q[x,y,z]

```

## Chapter 2

# Installation of the RingsForHomalg Package

To install this package just extract the package's archive file to the GAP `pkg` directory.

By default the RingsForHomalg package is not automatically loaded by GAP when it is installed. You must load the package with

```
LoadPackage( "RingsForHomalg" );
```

before its functions become available.

Please, send us an e-mail if you have any questions, remarks, suggestions, etc. concerning this package. Also, we would be pleased to hear about applications of this package.

The authors.

## Chapter 3

# The Ring Table

### 3.1 An Example for a Ring Table - Singular

todo: introductory text, mention: transposed matrices, the macros, refer to the philosophy

#### 3.1.1 BasisOfRowModule (in the homalg table for Singular)

◇ BasisOfRowModule (*M*)

(function)

##### Returns:

This is the entry of the homalg table, which calls the corresponding macro BasisOfRowModule (3.1.2) inside the computer algebra system.

Code

```
BasisOfRowModule :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NrColumns( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = BasisOfRowModule(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.BasisOfModule
  );

  return N;

end,
```

#### 3.1.2 BasisOfRowModule (Singular macro)

◇ BasisOfRowModule (*M*)

(function)

##### Returns:

Code

```

BasisOfRowModule := "\n\
proc BasisOfRowModule (matrix M)\n\
{\n\
    return(std(M));\n\
}\n\n",

```

### 3.1.3 BasisOfColumnModule (in the homalg table for Singular)

◇ BasisOfColumnModule ( $M$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro BasisOfColumnModule (3.1.4) inside the computer algebra system.

Code

```

BasisOfColumnModule :=
function( M )
    local N;

    N := HomalgVoidMatrix(
        NrRows( M ),
        "unknown_number_of_columns",
        HomalgRing( M )
    );

    homalgSendBlocking(
        [ "matrix ", N, " = BasisOfColumnModule(", M, ")" ],
        "need_command",
        HOMALG_IO.Pictograms.BasisOfModule
    );

    return N;

end,

```

### 3.1.4 BasisOfColumnModule (Singular macro)

◇ BasisOfColumnModule ( $M$ )

(function)

**Returns:**

Code

```

BasisOfColumnModule := "\n\
proc BasisOfColumnModule (matrix M)\n\
{\n\
    return(Involution(BasisOfRowModule(Involution(M))));\n\
}\n\n",

```

### 3.1.5 DecideZeroRows (in the homalg table for Singular)

◇ DecideZeroRows ( $A$ ,  $B$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro `DecideZeroRows` (3.1.6) inside the computer algebra system.

Code

```
DecideZeroRows :=
function( A, B )
  local N;

  N := HomalgVoidMatrix(
    NrRows( A ),
    NrColumns( A ),
    HomalgRing( A )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = DecideZeroRows(", A, B, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.DecideZero
  );

  return N;

end,
```

### 3.1.6 DecideZeroRows (Singular macro)

◇ `DecideZeroRows(A, B)`

(function)

**Returns:**

Code

```
DecideZeroRows := "\n\
proc DecideZeroRows (matrix A, matrix B)\n\
{\n\
  return(reduce(A,B));\n\
}\n\n",
```

### 3.1.7 DecideZeroColumns (in the homalg table for Singular)

◇ `DecideZeroColumns(A, B)`

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro `DecideZeroColumns` (3.1.8) inside the computer algebra system.

Code

```
DecideZeroColumns :=
function( A, B )
  local N;

  N := HomalgVoidMatrix(
    NrRows( A ),
    NrColumns( A ),
    HomalgRing( A )
  );
```

```

homalgSendBlocking(
  [ "matrix ", N, " = DecideZeroColumns(", A, B, ")" ],
  "need_command",
  HOMALG_IO.Pictograms.DecideZero
);

return N;

end,

```

### 3.1.8 DecideZeroColumns (Singular macro)

◇ DecideZeroColumns (A, B)

(function)

**Returns:**

Code

```

DecideZeroColumns := "\n\
proc DecideZeroColumns (matrix A, matrix B)\n\
{\n\
  return(Involution(reduce(Involution(A),Involution(B))));\n\
}\n\n",

```

### 3.1.9 SyzygiesGeneratorsOfRows (in the homalg table for Singular)

◇ SyzygiesGeneratorsOfRows (M)

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro SyzygiesGeneratorsOfRows (3.1.10) inside the computer algebra system.

Code

```

SyzygiesGeneratorsOfRows :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NrRows( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = SyzygiesGeneratorsOfRows(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

end,

```

### 3.1.10 SyzygiesGeneratorsOfRows (Singular macro)

◇ SyzygiesGeneratorsOfRows ( $M$ )

(function)

**Returns:**

```
Code
SyzygiesGeneratorsOfRows := "\n\
proc SyzygiesGeneratorsOfRows (matrix M)\n\
{\n\
  return(SyzForHomalg(M));\n\
}\n\n",
```

### 3.1.11 SyzygiesGeneratorsOfColumns (in the homalg table for Singular)

◇ SyzygiesGeneratorsOfColumns ( $M$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro SyzygiesGeneratorsOfColumns (3.1.12) inside the computer algebra system.

```
Code
SyzygiesGeneratorsOfColumns :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    NrColumns( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = SyzygiesGeneratorsOfColumns(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

end,
```

### 3.1.12 SyzygiesGeneratorsOfColumns (Singular macro)

◇ SyzygiesGeneratorsOfColumns ( $M$ )

(function)

**Returns:**

```
Code
SyzygiesGeneratorsOfColumns := "\n\
proc SyzygiesGeneratorsOfColumns (matrix M)\n\
{\n\
  return(Involution(SyzForHomalg(Involution(M))));\n\
}\n\n",
```

### 3.1.13 BasisOfRowsCoeff (in the homalg table for Singular)

◇ BasisOfRowsCoeff( $M$ ,  $T$ )

(function)

#### Returns:

This is the entry of the homalg table, which calls the corresponding macro BasisOfRowsCoeff (3.1.14) inside the computer algebra system.

```
Code
BasisOfRowsCoeff :=
function( M, T )
  local v, N;

  v := homalgStream( HomalgRing( M ) )!.variable_name;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NrColumns( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [
      "list ", v, "l=BasisOfRowsCoeff(", M, "); ",
      "matrix ", N, " = ", v, "l[1]; ",
      "matrix ", T, " = ", v, "l[2]"
    ],
    "need_command",
    HOMALG_IO.Pictograms.BasisCoeff
  );

  return N;

end,
```

### 3.1.14 BasisOfRowsCoeff (Singular macro)

◇ BasisOfRowsCoeff( $M$ ,  $T$ )

(function)

#### Returns:

```
Code
BasisOfRowsCoeff := "\n\
proc BasisOfRowsCoeff (matrix M)\n\
{\n\
  matrix B = std(M);\n\
  matrix T = lift(M,B);\n\
  list l = B,T;\n\
  return(l)\n\
}\n\n",
```

### 3.1.15 BasisOfColumnsCoeff (in the homalg table for Singular)

◇ BasisOfColumnsCoeff( $M$ ,  $T$ )

(function)

#### Returns:



This is the entry of the homalg table, which calls the corresponding macro BasisOfColumnsCoeff (3.1.16) inside the computer algebra system.

Code

```

BasisOfColumnsCoeff :=
function( M, T )
  local v, N;

  v := homalgStream( HomalgRing( M ) )!.variable_name;

  N := HomalgVoidMatrix(
    NrRows( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [
      "list ", v, "l=BasisOfColumnsCoeff(", M, "); ",
      "matrix ", N, " = ", v, "l[1]; ",
      "matrix ", T, " = ", v, "l[2]"
    ],
    "need_command",
    HOMALG_IO.Pictograms.BasisCoeff
  );

  return N;

end,

```

### 3.1.16 BasisOfColumnsCoeff (Singular macro)

◇ BasisOfColumnsCoeff(*M*, *T*)

(function)

**Returns:**

Code

```

BasisOfColumnsCoeff := "\n\
proc BasisOfColumnsCoeff (matrix M)\n\
{\n\
  list l = BasisOfRowsCoeff(Involution(M));\n\
  matrix B = l[1];\n\
  matrix T = l[2];\n\
  l = Involution(B),Involution(T);\n\
  return(l);\n\
}\n\n",

```

### 3.1.17 DecideZeroRowsEffectively (in the homalg table for Singular)

◇ DecideZeroRowsEffectively(*A*, *B*, *T*)

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro DecideZeroRowsEffectively (3.1.18) inside the computer algebra system.

```

Code
DecideZeroRowsEffectively :=
function( A, B, T )
  local v, N;

  v := homalgStream( HomalgRing( A ) )!.variable_name;

  N := HomalgVoidMatrix(
    NrRows( A ),
    NrColumns( A ),
    HomalgRing( A )
  );

  homalgSendBlocking(
    [
      "list ", v, "l=DecideZeroRowsEffectively(", A, B, "); ",
      "matrix ", N, " = ", v, "l[1]; ",
      "matrix ", T, " = ", v, "l[2]"
    ],
    "need_command",
    HOMALG_IO.Pictograms.DecideZeroEffectively
  );

  return N;

end,

```

### 3.1.18 DecideZeroRowsEffectively (Singular macro)

◇ DecideZeroRowsEffectively(*A*, *B*, *T*)

(function)

**Returns:**

```

Code
DecideZeroRowsEffectively := "\n\
proc DecideZeroRowsEffectively (matrix A, matrix B)\n\
{\n\
  matrix M = reduce(A,B);\n\
  matrix T = lift(B,M-A);\n\
  list l = M,T;\n\
  return(l);\n\
}\n\n",

```

### 3.1.19 DecideZeroColumnsEffectively (in the homalg table for Singular)

◇ DecideZeroColumnsEffectively(*A*, *B*, *T*)

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro DecideZeroColumnsEffectively (3.1.20) inside the computer algebra system.

```

Code
DecideZeroColumnsEffectively :=
function( A, B, T )
  local v, N;

```

```

v := homalgStream( HomalgRing( A ) )!.variable_name;

N := HomalgVoidMatrix(
  NrRows( A ),
  NrColumns( A ),
  HomalgRing( A )
);

homalgSendBlocking(
  [
    "list ", v, "l=DecideZeroColumnsEffectively(", A, B, "); ",
    "matrix ", N, " = ", v, "l[1]; ",
    "matrix ", T, " = ", v, "l[2]"
  ],
  "need_command",
  HOMALG_IO.Pictograms.DecideZeroEffectively
);

return N;

end,

```

### 3.1.20 DecideZeroColumnsEffectively (Singular macro)

◇ DecideZeroColumnsEffectively(*A*, *B*, *T*)

(function)

**Returns:**

```

Code
DecideZeroColumnsEffectively := "\n\
proc DecideZeroColumnsEffectively (matrix A, matrix B)\n\
{\n\
  list l = DecideZeroRowsEffectively(Involution(A),Involution(B));\n\
  matrix B = l[1];\n\
  matrix T = l[2];\n\
  l = Involution(B),Involution(T);\n\
  return(l);\n\
}\n\n",

```

### 3.1.21 RelativeSyzygiesGeneratorsOfRows (in the homalg table for Singular)

◇ RelativeSyzygiesGeneratorsOfRows(*M*, *M2*)

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro RelativeSyzygiesGeneratorsOfRows (3.1.22) inside the computer algebra system.

```

Code
RelativeSyzygiesGeneratorsOfRows :=
function( M, M2 )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",

```

```

    NrRows( M ),
    HomalgRing( M )
);

homalgSendBlocking(
  [ "matrix ", N, " = RelativeSyzygiesGeneratorsOfRows(", M, M2, ")" ],
  "need_command",
  HOMALG_IO.Pictograms.SyzygiesGenerators
);

return N;

end,

```

### 3.1.22 RelativeSyzygiesGeneratorsOfRows (Singular macro)

◇ RelativeSyzygiesGeneratorsOfRows( $M$ ,  $M2$ )

(function)

**Returns:**

```

Code
RelativeSyzygiesGeneratorsOfRows := "\n\
proc RelativeSyzygiesGeneratorsOfRows (matrix M1, matrix M2)\n\
{\n\
  return(std(modulo(M1, M2))); \n\
}\n\n",

```

### 3.1.23 RelativeSyzygiesGeneratorsOfColumns (in the homalg table for Singular)

◇ RelativeSyzygiesGeneratorsOfColumns( $M$ ,  $M2$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro RelativeSyzygiesGeneratorsOfColumns (3.1.24) inside the computer algebra system.

```

Code
RelativeSyzygiesGeneratorsOfColumns :=
function( M, M2 )
  local N;

  N := HomalgVoidMatrix(
    NrColumns( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = RelativeSyzygiesGeneratorsOfColumns(", M, M2, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

end,

```

### 3.1.24 RelativeSyzygiesGeneratorsOfColumns (Singular macro)

◇ RelativeSyzygiesGeneratorsOfColumns( $M$ ,  $M2$ )

(function)

**Returns:**

```
Code
RelativeSyzygiesGeneratorsOfColumns := "\n\
proc RelativeSyzygiesGeneratorsOfColumns (matrix M1, matrix M2)\n\
{\n\
  return(Involution(RelativeSyzygiesGeneratorsOfRows(Involution(M1), Involution(M2))));\n\
}\n\n",
```

### 3.1.25 ReducedSyzygiesGeneratorsOfRows (in the homalg table for Singular)

◇ ReducedSyzygiesGeneratorsOfRows( $M$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro ReducedSyzygiesGeneratorsOfRows (3.1.26) inside the computer algebra system.

```
Code
ReducedSyzygiesGeneratorsOfRows :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NrRows( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = ReducedSyzygiesGeneratorsOfRows(", M, ") " ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

end,
```

### 3.1.26 ReducedSyzygiesGeneratorsOfRows (Singular macro)

◇ ReducedSyzygiesGeneratorsOfRows( $M$ )

(function)

**Returns:**

```
Code
ReducedSyzForHomalg := "\n\
proc ReducedSyzForHomalg (matrix M)\n\
{\n\
  return(matrix(nres(M,2)[2]));\n\
}\n\n",
```

### 3.1.27 ReducedSyzygiesGeneratorsOfColumns (in the homalg table for Singular)

◇ ReducedSyzygiesGeneratorsOfColumns ( $M$ ) (function)

#### Returns:

This is the entry of the homalg table, which calls the corresponding macro ReducedSyzygiesGeneratorsOfColumns (3.1.28) inside the computer algebra system.

Code

```

ReducedSyzygiesGeneratorsOfColumns :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    NrColumns( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = ReducedSyzygiesGeneratorsOfColumns(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

end,
```

### 3.1.28 ReducedSyzygiesGeneratorsOfColumns (Singular macro)

◇ ReducedSyzygiesGeneratorsOfColumns ( $M$ ) (function)

#### Returns:

Code

```

ReducedSyzygiesGeneratorsOfRows := "\n\
proc ReducedSyzygiesGeneratorsOfRows (matrix M)\n\
{\n\
  return(ReducedSyzForHomalg(M));\n\
}\n\n",
```

# References

[ht09] T. homalg team. *The homalg project*, 2003-2009. <http://homalg.math.rwth-aachen.de/>. 5

# Index

RingsForHomalg, 5

BasisOfColumnModule

in the homalg table for Singular, 11

Singular macro, 11

BasisOfColumnsCoeff

in the homalg table for Singular, 15

Singular macro, 16

BasisOfRowModule

in the homalg table for Singular, 10

Singular macro, 10

BasisOfRowsCoeff

in the homalg table for Singular, 15

Singular macro, 15

DecideZeroColumns

in the homalg table for Singular, 12

Singular macro, 13

DecideZeroColumnsEffectively

in the homalg table for Singular, 17

Singular macro, 18

DecideZeroRows

in the homalg table for Singular, 11

Singular macro, 12

DecideZeroRowsEffectively

in the homalg table for Singular, 16

Singular macro, 17

ReducedSyzygiesGeneratorsOfColumns

in the homalg table for Singular, 21

Singular macro, 21

ReducedSyzygiesGeneratorsOfRows

in the homalg table for Singular, 20

Singular macro, 20

RelativeSyzygiesGeneratorsOfColumns

in the homalg table for Singular, 19

Singular macro, 20

RelativeSyzygiesGeneratorsOfRows

in the homalg table for Singular, 18

Singular macro, 19

SyzygiesGeneratorsOfColumns

in the homalg table for Singular, 14

Singular macro, 14

SyzygiesGeneratorsOfRows

in the homalg table for Singular, 13

Singular macro, 14